



1. Identification code of the product type / Trademark:

**PW PUR - D 40/82**

Roof sandwich panel with PUR core, marked with the symbol PW PUR-D 40/82, modular width 1050 [mm] and thickness 40 [mm]

2. Application of the product:

Self-supporting, double metal faced insulating sandwich panels, intended to be fixed to supporting structure, for roof covers.

3. Producer:

Paneltech Sp. z o.o., 41-508 Chorzów, ul. Michałkowicka 24.

4. Evaluation and verification system of product performances

Conformity valuation system 3 was applied according to the requirements of the norms EN 13172 and EN 14509.

5. Harmonized norm / Notified bodies:

Harmonized norm: PN-EN 14509:2013-12

Notified bodies responsible for product type tests:

Building Research Institute in Warsaw – No. 1488

and Institute of Mechanised Construction and Rock Mining – No. 1454.

6. Declared values of steel facings

External facing 0,5 mm, internal facing 0,5 or 0,4 mm;

R- minimum yield strength of steel faces 220 MPa;

Duplex system for corrosion protection – two protection layers: metallic and organic, for corrosion category RC3, atmosphere with low content of SO<sub>2</sub>.

7. Declared values

PW PUR – D 40/82			
Apparent core density	40 kg/m <sup>3</sup> +/-3 kg/m <sup>3</sup>	Thermal conductivity $\lambda_D$	0,023 W/m K
		Thermal transmittance $U_{d,s}$	0,50 W/(m <sup>2</sup> K)
Tensile strength	110 kPa	Thermal transmittance of a panel U	0,48 W/(m <sup>2</sup> K)
Tensile E-modulus	3,30 MPa	Fire reaction class	NPD
Compressive strength	120 kPa	External fire exposure of roof	$B_{roof}(t1)$
Compressive E-modulus	2,80 MPa	Roof fire resistance class	NPD
Shear strength	120 kPa	Water permeability	B
Shear E-modulus	2,80 MPa	Air permeability	$\leq 5 \text{ m}^3/\text{h/m}^2$
Wrinkling stress for time t= 2000 h	1,47 [-]	Water vapour permeability	impermeable
Wrinkling stress for time t= 10 000 h	2,40 [-]	Acoustic insulation $R_w(C,C_{it})$	26 (-2;-5) dB
Characteristic values for mechanical properties	BPEC Report	Durability, long term mechanical properties	all colours meet the requirements

Product meets the tolerances according to the norm EN 14509, Annex D. Summary thermal transmittance  $U_c$  for the panels includes type of the panel joints, facing profiles, mechanical fasteners and foam aging according to the Chapter A.10. Thermal transmittance U refers to sandwich panel as building element and characteristic values for mechanical properties included in Report BPEC are in accordance with Chapter 5.

8. Summary:

Performance of above mentioned product is in conformity with the declared performances.

This declaration of performance is issued in accordance with Regulation (EC) No 305/2011 and 574/2014 of the European Parliament under the sole responsibility of the producer identified above.

Signed on behalf of the producer:



Chorzów, 04.04.2016

WICEPREZES ZARZĄDU

mgr inż. Marek Romański