



## 1. Identification code of the product type / Trademark:

**PW PUR - S 60**

Sandwich panel type „wall panel with visible joint” with PUR core, marked with the symbol PW PUR-S 60, modular width 1130 [mm], optional 1000 [mm] or 1050 [mm] and thickness 60 [mm]

## 2. Application of the product:

Self-supporting, double metal faced insulating sandwich panels, intended to be fixed to supporting structure, for partition and external walls.

## 3. Producer:

Paneltech Sp. z o.o., 41-508 Chorzów, ul. Michałkowicka 24.

## 4. Evaluation and verification system of product performances

Conformity valuation system 3 was applied according to the requirements of the norms EN 13172 and EN 14509.

## 5. Harmonized norm / Notified bodies:

Harmonized norm: PN-EN 14509:2013-12

Notified bodies responsible for product type tests:

Building Research Institute in Warsaw – No. 1488

and Institute of Mechanised Construction and Rock Mining – No. 1454.

## 6. Declared values of steel facings

External facing 0,5 mm, internal facing 0,5 or 0,4 mm;

R- minimum yield strength of steel faces 220 MPa;

Duplex system for corrosion protection – two protection layers: metallic and organic, for corrosion category RC3, atmosphere with low content of SO<sub>2</sub>.

## 7. Declared values

PW PUR – S 60			
Thermal conductivity $\lambda_D$	0,023 W/m K	Apparent core density	40 kg/m <sup>3</sup> +/-3 kg/m <sup>3</sup>
Thermal transmittance of a panel U	0,36 W/(m <sup>2</sup> K)	Thermal transmittance U <sub>c</sub>	0,38 W/(m <sup>2</sup> K)
Tensile strength	110 kPa	Fire reaction class	„E”, B-s2, d0
Tensile E-modulus	3,30 MPa	Fire resistance class to external fire	NRO
Compressive strength	120 kPa	Wall fire resistance class	NPD
Compressive E-modulus	2,80 MPa	Water permeability	B
Shear strength	120 kPa	Air permeability	≤5 m <sup>3</sup> /h/m <sup>2</sup>
Shear E-modulus	2,80 MPa	Water vapour permeability	impermeable
Acoustic insulation R <sub>w</sub> (C,C <sub>tr</sub> )	26 (-3;-4) dB	Durability, long term mechanical properties	all colours meet the requirements
<p>Product meets the tolerances according to the norm EN 14509, Annex D. Summary thermal transmittance U<sub>c</sub> for the panels includes type of the panel joints, facing profiles, mechanical fasteners and foam aging according to the Chapter A.10. Thermal transmittance U refers to sandwich panel as building element and characteristic values for mechanical properties included in Report BPEC are in accordance with Chapter 5.</p>			

## 8. Summary:

Performance of above mentioned product is in conformity with the declared performances. This declaration of performance is issued in accordance with Regulation (EC) No 305/2011 and 574/2014 of the European Parliament under the sole responsibility of the producer identified above.

Signed for on behalf of the producer: